



Milosava Vlajića 49
Sopot, 11450 SERBIA, EUROPE

www.eg-prometal.rs

Stationary model	Economic 300	Economic 400D	Economic 400DF	Universal 400 FA	Universal 600 FA	Universal 1000 FA
Capacity for hollow blocks 19x19x39 cm /h	240	350	350	600	900	1500
Capacity for paving stones m2/8h	120-150	150	250	300	500	800-1000
Automation type	Semiautomatic	Semiautomatic	Semiautomatic	Semi or full automatic	Full Automatic	Full Automatic
Useful mould area (mm)	650 x 520	1100 x 500	1100 x 500	1250 x 500	1200 x 650	1200 x 800
Production pallet size (mm), Height 50 mm	1100 x 500	1200 x 550	1200 x 550		1400 x 700	1400 x 900
Concrete hopper volume (l)	300	600	600	900	1000	1300
Concrete hopper volume 2 (l)	-	-		750	800	900
Max. block height (mm)	330	330	330	330	330	330
Min. block height (mm)	50	50	50	40	50	40
Operation cycle/sec	45-50	40	30	20-25	20-25	20-25
Total installed electric power (kW)	5,5	12		16	20,5	22,5
Weight (kg)	2500	3000	4500	6000	13000	14500

www.eg-prometal.rs

2013.Feb.